MNR-18N16000A

SKU: 234748



* PAS * 500 From

NCH of Daylor folker Revenue:

 $\label{eq:Hybrid} \mbox{Hybrid HD Video Recorder 16-channel analogue,} \\ \mbox{8-ch. IP HDMI, 2xSATA, w/o HDD}$

Main Features

| PTZ control via coaxial (UTC) |
|--|
| Audio/Alarm inputs and outputs |
| USB 2.0, eSATA and RS-485 interface |
| P Compression methods: H.264, H.265 |
| Remote access via app, browser and CMS |
| USB mouse included |
| |

Specifications

| Dimensions (HxWxD) | 380x340x50mm |
|---------------------------|----------------|
| Series | eneo IN-Series |
| Blower | no |
| Video inputs (amount) | 16 |
| Channels total | 24 |
| IP channels | 8 (24 IP only) |
| Max. recording resolution | 3840x2160 |
| Recording rate max. | 480 fps |
| Recording rate max.2 | @1920x1080 |
| Compression | H.264, H.265 |

MNR-18N16000A

Continuation of the specifications

| Main video outputs | HDMI (4K), VGA |
|-----------------------------|---|
| Spot monitor | composite (CVBS) |
| Network | 100/1000 Base-T, RJ45 |
| Alarm inputs 2 | 16 |
| Alarm outputs | 1 |
| Audio inputs | 16 |
| Serial interfaces | Coaxitron (HD Protocol), RS-485 |
| Max. internal HDD capacity | 20 TB |
| Internal HDD capacity | 0 TB |
| Interfaces external storage | 1x eSATA, USB |
| HDD slots | 2x SATA |
| HDD hotswap | no |
| RAID | n/a |
| Data tranfer rate max. | 256 Mbps |
| Analysis functions | Additional functions depending on connected IP camera, Audio detection, Face recognition, Intrusion, Line detection, Object classification (person / vehicle), Obstruction detection, The recorder hardware (on board) provides the following analysis functions for analog cameras |
| Remote access | Microsoft Internet Explorer, remote software |
| Operation mode | Pentaplex |
| 19" rack mount | no |
| Power consumption | 20W, without HDD |
| Operating temperature | 0°C ~ +40°C |
| ONVIF | ONVIF Profile S, yes |
| Signal format | AHD @ 8MP, Composite (FBAS), HD-TVI @ 8MP, IP @ 8MP |
| Weight | 2.3kg |
| Colour | black |
| Housing | Metal/Plastic |
| Playback | 16 channel split, 4 channel split, 8 channel split, full screen |
| Data transfer rate incoming | 64 Mbps |
| Audio output | RCA |
| Operating system | Linux |
| Manufacturer order number | 234748 |

Optional Accessory

| SKU | Name | Description |
|--------|--------------|---|
| 234989 | eneo INsight | Control software for recorder IN- and MN-series |

MNR-18N16000A

Continuation of accessory

| 236197 | eneo INsight Evidence Locker | For the research of HDD's for recorders of IN-series |
|--------|------------------------------|--|
| 236196 | eneo INsight Evidence Player | For replay of exported data for recorder IN-series IN-Serie |
| 234990 | eneo INsight mobile | Mobile App for recorder IN- and MN-series |
| 217658 | HDD-2000SATA Purple | Hard Disk Drive 2TB, SATA, for eneo Video Recorders, expansion |
| 217657 | HDD-3000SATA Purple | Hard Disk Drive 3TB, SATA, for eneo Video Recorders, expansion |
| 217659 | HDD-4000SATA Purple | Hard Disk Drive 4TB, SATA, for eneo Video Recorders, expansion |
| 217660 | HDD-6000SATA Purple | Hard Disk Drive 6TB, SATA, for eneo Video Recorders, expansion |

Optional Services

| SKU | Name | Description |
|--------|-------------------|--|
| 229228 | LCUN-eneo-KUIN-UX | Preconfiguration 1x eneo recorder1x eneo IE with up to 8 eneo IP cameras |
| 229235 | CON-KOMP | Compatibility check for cameras, NVR, VMS systems (one pair of devices) |

Your contact person

SLD Security & Communications Ltd. 101 Eden Grove Road KT14 7PX Byfleet Surrey GB

Tel: +44.7973112104 E-Mail: enquiries@sld.uk

Web: www.sld.uk



Secure by Design