



MPD-62V2713P0A

SKU: 233014



1/2,8" HD Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, Indoor

Main Features

-
- 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
-
- Compact plastic housing for indoor use
-
- Resolution max. 1920x1080 (Full HD)
-
- Multisignal: HD-TVI, AHD, CVI, Composite selectable
-
- Variofocal 2.8~12mm day&night lens
-
- LSC (Lens shading compensation)
-

-
- Removable infrared cut filter
-
- 3D-DNR noise reduction
-
- Digital Wide Dynamic Range (D-WDR)
-
- Integral motion detection
-
- Wedge adapter included (10° inclination)
-
- Scratch resistant hard coated bubble
-

Specifications

Dimensions (HxWxD)	100x116mm
Series	eneo KX-Series
Resolution Pixels	1920x1080
Resolution Pixels	960x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night Switch	ICR
Sensitivity	0,3 Lux
Sensitivity 2	40IRE, at F1.3

MPD-62V2713P0A

Continuation of the specifications

Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Lens Type 2	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
Illumination	infrared
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Video outputs	AHD, composite (CVBS), CVI, HD-TVI
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Mounting_4	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Camera built	Dome
Frame Rate	25/30fps @ 1920x1080p
Aperture range (F)	F1,3
Illumination range	approx. 30m
Weight	260g
Manufacturer order number	233014

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output

MPD-62V2713P0A

Continuation of accessory

220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

Optional Services

SKU	Name	Description
229233	CON-KAM-AKON	Preconfiguration 1x analog camera Function test, FW update
211125	CUS-SL-F	Extra charge for special paint fixed dome in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

Your contact person

SLD Security & Communications Ltd.
 101 Eden Grove Road
 KT14 7PX Byfleet Surrey
 GB
 Tel: +44.7973112104
 E-Mail: enquiries@sld.uk
 Web: www.sld.uk



SLD Security & Communications
 Secure by Design