



## NXB-980IR3516M

Article number: 210473

1/2.8" Network Camera, PoE, 1920x1080, ONVIF, Day&Night, BLC, AWB, 3.5-16mm, Infrared

### Mainfeatures

1/2.8" 2.0 MP Progressive Scan CMOS-Sensor

Triple Streaming (H.264, MPEG4, MJPEG)

Noise Reduction (2D-DNR)

Auto Exposure (AE)

Cross Web-Browsing, ONVIF

Framerate increase on motion detection

Resolution max. 1920x1080 (Full HD)

True Day & Night (TDN)

Back Light Compensation (BLC)

Auto White Balance (AWB)

Privacy Masking, Password Protection, IP Filter

OpenVPN Support

### Specifications

Series	eneo Economy Class
Resolution standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	Sony Exmor
Imager	CMOS
Sensitivity	0,2 Lux
Sensitivity	(colour) 0.0 Lux (B&W) at F1.8
Digital Noise Reduction (DNR)	yes
Digital Noise Reduction (DNR)	2D-DNR
Low speed shutter	yes
White balance	AWB

# NXB-980IR3516M

## Specifications continued

Backlight compensation	BLC
Wide Dynamic Range (WDR)	no
IR cut filter	switchable
Mirror function	yes
Resolution max.	1920x1080
Resolution	1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 720x576 (4:3), 704x480 (4:3), 640x480 (4:3), 352x288 (4:3), 352:240 (4:3), 320x240 (4:3)
Image transmission rate max.	30 fps
Privacy zones masking	8 zones masking
Activity detection	yes, 8 zones
Menu languages	German, French, Russian, Chinese, Korean, English
External connections	voltage input
Audio support	no
Alarm inputs	no
Alarm outputs	no
Alarm processing	SD-card recording, FTP, E-Mail, HTTP, HTTP/XML, Boost
Internal storage	microSDHC card, 32GB
Compression standard	H.264, MPEG-4, M-JPEG, JPEG
Stream types	2x H.264, 1x MJPEG multiple
Ethernet interface	100Base-TX
Web browser	MS Internet Explorer vers. 7.0 or higher, Google Chrome (Java), Mozilla Firefox (Java), Safari (Java)
Network protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, RTP, RTSP, NTP, DHCP, SMTP, DDNS, RTCP, FTP, NFS, CIFS, UPnP, Zeroconf, Bonjour, SSL, OpenVPN, NAT
Serial interfaces	no
Multicast compliant	yes
Lens type	varifocal
Focal length	3,5 - 16 mm
Horizontal angle of view	85 - 26 °
Digital zoom	yes
Illumination	infrared
Illumination	24x LED 850nm, 76°
Illumination range	approx. 20m
Remote configuration	web browser
Password protection	yes
e-PTZ support	yes
Supply voltage	PoE, 12VDC
Power over Ethernet	IEEE 802.3af
Power consumption	6.0W max.
Temperature range (operation)	-20°C ~ +50°C
Vandalism resistant	no
Housing	outdoor
Housing material	metal
Colour (housing)	white

# NXB-980IR3516M

## Specifications continued

Protection rating	IP67
Sunshield	yes
Hidden cable management	yes
SDK	upon request
ONVIF	Profile S
Certificates	CE, RoHS
Dimensions (HxWxD)	66x66x198mm
Parts supplied	mounting accessories, installation CD, drilling template, Quick Installation Guide, Manual and Software on CD-ROM
Remarks	Mind limited temperature range for outdoor usage
Mount	Wall mount bracket included

# NXB-980IR3516M

## Available Accessories

Bild	Art. Nr. / Bezeichnung	Beschreibung
	203658 / VT-PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1.0A), Regulated, with DC Plug
	211974 / ENX-900P	PoE Extender, RJ45, Indoor, up to 100m, Gigabit Ethernet, Half/Full Duplex
	211980 / EVX-900R	Media Converter, Indoor, Transmitter-Receiver, 1x RJ45, 1x RJ-11, 12V, up to 1000m
	211981 / EVX-900B	Media Converter, indoor, Transmitter-Receiver, 1x RJ45, 1x BNC, 12V, up to 1000m
	211976 / ECB-1	Media Converter, Indoor, 1x RJ45, 1x SFP
	211979 / ENI-900P	PoE Injector, Gigabit, Indoor, PoE+, RJ45
	211982 / EPS-1008	PoE Switch, 8x PoE+, 1x RJ45, 1x SFP, 130W, Metal Housing
	211983 / EPS-1016	PoE Switch, 16x PoE+, 2x RJ45, 2x SFP, 250W, 19" Rack

## Your Contact Person

SLD Security & Communications  
4 Mays Close, Weybridge, Surrey KT13 0XL England  
Phone +44.1483225633 Fax +44.1483225634  
enquiries@sld.uk <http://sld.uk/>