



# MPB-72M0550M0A

SKU: 217718



1/2,8" HD Camera, Day&Night, 1920x1080, Infrared, WDR, 5-50mm, 12/24V, IP67

Abb. ähnlich

## Main Features

- 1/2,8" 2 Megapixel SONY STARVIS CMOS-Sensor
- Resolution max. 1920x1080 (Full HD)
- Separate outputs for digital and multi-signal
- Multisignal: HD-TVI, AHD, CVI and Composite selectable
- Digital signal: EX-SDI, HD-SDI selectable
- Motorized lens 5 ~ 50mm

- Removable infrared cut filter
- ROI (Region of Interest) WDR mode
- Integrated motion detector, defog, privacy zones
- IP67, built heater
- Easy installation, central locking screw
- IR illumination switchable via OSD menu

## Specifications

Dimensions (HxWxD)	100x107,8x277mm
Series	eneo Candid Medium, eneo COAXIZE, eneo KX-Series
Resolution Pixels	1280x720, 1920x1080, 720x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night Switch	ICR
Sensitivity	0,08 Lux
Sensitivity 2	40IRE, at F1.4
Low Speed Shutter	yes

# MPB-72M0550M0A

Continuation of the specifications

Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	WDR 113dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	5 - 50 mm
Iris Control	DC
Zoom Factor	10x
Digital Zoom	no
Horizontal Angle of View	45 - 7°
Vertical Angle of View	25 - 4°
Illumination	infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium
Heater	yes
Video outputs	AHD, composite (CVBS), CVI, EX-SDI, HD-SDI, HD-TVI
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Mounting_4	Ceiling mount, Wall mount
Supply voltage	12VDC, 24VAC
Power consumption	10.5W
Vandal proof	no
Operating temperature	-30°C ~ +50°C
Protection rating	IP67
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, EX-SDI (270 Mbps), HD-SDI (1.485 Gbps), HD-TVI @ 2MP
Camera built	Bullet
Frame Rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Aperture range (F)	F1.6
Illumination range	approx. 60m
Weight	1.35kg
Manufacturer order number	217718

## Optional Accessory

SKU	Name	Description
-----	------	-------------

# MPB-72M0550M0A

## Continuation of accessory

202888	AK-4	Camera junction box, for Candid Small ,Candid Medium, Series
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

## Optional Services

SKU	Name	Description
229233	CON-KAM-AKON	Preconfiguration 1x analog camera Function test, FW update
211123	CUS-SL-B	Extra charge for special paint bullet camera in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

## Your contact person

SLD Security & Communications Ltd.  
 101 Eden Grove Road  
 KT14 7PX Byfleet Surrey  
 GB  
 Tel: +44.7973112104  
 E-Mail: [enquiries@sld.uk](mailto:enquiries@sld.uk)  
 Web: [www.sld.uk](http://www.sld.uk)



SLD Security & Communications  
**Secure by Design**